



# Pressure cup spray gun

## 3000 DV / DVR

Art. no.: 30001 / 30411 / 30112 / 30401



Illustration shows 3000 FGR

Thank you very much for the trust you have placed in us and our products.



**Please read the operating manual first before working with the pressure cup gun.**

This operating and maintenance manual contains important information required for the safe and trouble-free operation of your pressure cup gun. Therefore, always keep this operating manual with the pressure cup gun.

**General notice:**

This pressure cup gun was developed for certain applications. We explicitly point out that this pressure cup gun must not be modified and/or used in a way that does not correspond to its intended use.

**Content:**

1. Technical data .....	3
2. Extent of delivery .....	3
3. Intended use .....	3
4. Features .....	3
5. Safety instructions .....	3
6. Installation / end of work .....	5
7. Maintenance and care .....	5
8. Storage .....	6
9. Troubleshooting .....	6
10. Warranty terms .....	7
11. Address .....	7
12. EC-declaration of conformity .....	8
13. Spare parts list .....	9
14. Notices .....	10

## 1. Technical data

Description	3000 DV	3000 DVR
Operating pressure	2-8 bar	2-8 bar
Maximum pressure	8 bar	8 bar
Container volume	1.400 ml	1.400 ml
1 Litre bottles	with plastic thread	with plastic thread
Connection thread Air	¼"	¼"
Compressed air supply	Via quick coupling	Via quick coupling
Adjustable spray pattern	3 times	3 times
Measurement 3000 DV / DVR	391 x 207 x 95 mm	391 x 207 x 95 mm
Measurement cardboard	415 x 247 x 110 mm	415 x 247 x 110 mm
Net weight	approx. 1485 g	approx. 1503 g
Gross weight	approx. 1809 g	approx. 1827 g
Weight hose set 3900 WH 02/04	150 g *	150 g *
Required air quality	filtered, condensate-free	filtered, condensate-free

\* included with 3000 DV-Set and 3000 DVR-Set

## 2. Extent of delivery

Pressure cup gun, compressed air connection, operating manual.

Additionally included with 3000 DVR-Set: Hose set 3900 WH 02 or 04.

## 3. Intended use

This pressure cup gun is a compressed air operated quality tool for professional use. It is suitable for processing liquid media in the form of commercially available 1 litre cans.

## 4. Features

The effectiveness of the pressure cup gun 3000 DV / DVR is based on overpressure. For this purpose, pressure is built up in the pressure container by means of an air pressure integrated in the gun body. This transports the material present in the pressure container via a riser pipe to the material nozzle. At the material nozzle the adjustable spraying air causes a mixing with the medium whereby an adjustable spraying jet develops.

## 5. Safety instructions



**This pressure cup gun is not suitable for alkaline and acidic media.**

**Such media must not be processed with this pressure cup gun!!!**

Protect yourself and the environment by taking appropriate precautions against the risk of accidents and observe the following instructions in your own interest:



- The operator must ensure proper operation.
- Do not bring compressed air and/or medium into contact with skin or eyes.
- Never direct the spray jet at animals, people or yourself.
- Keep children and pets away from the operating area.
- No manipulations, emergency repairs or misappropriations may be carried out on the pressure cup gun.
- Pressure cup guns may only be operated and maintained by instructed persons.
- Repairs must only be carried out by qualified persons.

**The following applies to all maintenance and repair work:**



- It is essential to disconnect the pressure cup gun from the compressed air connection before carrying out maintenance or repair work.
- Only use original spare parts.
- The maximum working pressure must not be exceeded (see point 1 "Technical data"). The working pressure must be adjusted via a (filter) pressure reducer.
- Only use compressed air as energy source.
- The compressed air connection may only be made via a quick coupling.
- When working with the pressure cup gun, wear the necessary protective clothing, protective goggles, work gloves, ear protection if necessary and a respirator mask.
- If there are leaks in the device or other operating faults, the device must be disconnected from the compressed air supply immediately and the cause of the fault must be eliminated.
- Open fire, sparks or smoking is prohibited.
- Beware of flammable materials.
- Processed media and cleaning media must be disposed of in an environmentally friendly manner.
- The disposal of the compressed air device must be carried out according to the valid legal regulations.

## 6. Installation/end of work

Preparing the gun for the first start-up: Screw in the compressed air connection and tighten it firmly using a 13 mm open-end or ring spanner, if necessary glue it in place. *For the optional pressure regulator instead of the air volume regulator:* Screw the pressure gauge included in the extent of delivery into the pressure regulator, glue it in if necessary.

Start-up: Unscrew the pressure container. Pierce the protective film of the 1 litre can and place it in the pressure container. Then dip the riser pipe into the medium and screw the pistol with the container lid hand-tight onto the pressure container. Do not use any tools for this! Connect the gun to the compressed air supply via the quick coupling. By pressing the trigger you put the pressure cup pistol into operation.



### Attention:

Wear heat-resistant gloves when using heated media. Danger of burns!

The spray pattern can be influenced by the following factors:

- Material quantity via stop screw/nozzle needle
- Adjusting the intake pressure
  - Spraying air via knurled screw on gun head
  - For fine jet - add a lot of air
  - For coarse jet - add little air
- Distance between spray nozzle and object
- Angle of the gun to the object

End of work: Vent the pressure container using the exhaust valve - pos. 24 (only for 3000 DVR). Disconnect the device from the compressed air supply after each use. Clean the device according to the instructions given in point 7.



### Attention:

Never operate the trigger while the container is under pressure but the pressure cup gun is not connected to the compressed air source. This can push the medium into the air ducts and render the pressure cup gun unusable!

## 7. Maintenance and care

Clean the compressed air device after each use. Fill the pressure tank with cleaning medium and flush the pressure cup gun and the hoses (if present) by starting the device.

We recommend benzine or commercially available turpentine-based cleaners.

**Do not use aggressive cleaning media!** Following the maintenance instructions will ensure a long service life and trouble-free operation for this quality product.

**Attention:**

Pay attention to a proper disposal of the residues, which arise during the maintenance and care.

**8. Storage**

The compressed air tool must be stored under the following conditions:

- If residual material is present, store only upright.
- Carefully clean the pressure cup gun after each use.
- Store in a dry and dust-free place.
- Do not expose to liquids and/or aggressive chemicals.
- Keep out of the reach of children.

**9. Troubleshooting**

In all cases of malfunction, please first check whether there is sufficient compressed air available, whether the spray material can still be processed, whether the expiry date has passed or whether the material has dried out.

- **Gun sprays messy**

Possible cause: Adjustment options not optimally adjusted.

Solution: Operating pressure, spraying air, material quantity to be adjusted to each other.

- **Gun does not spray any material**

Possible cause: The riser pipe and/or spray nozzle are clogged.

Solution: Clean clogged parts.

- **Air escapes from the spray nozzle even though the trigger is in its initial position.**

Possible cause: Valve bolt is jammed.

Solution: Pour oil onto the valve bolt and/or into the compressed air intake. Operate the trigger several times.

- **Material exits the spray nozzle even though the trigger is in its initial position.**

Possible cause: Nozzle needle is jammed.

Solution: Clean the nozzle needle, apply oil to the nozzle needle and/or slightly reduce the pressure on the nozzle needle seal using a 9mm wrench. In order to ensure error-free use, a clamping effect on the nozzle needle seal must remain. Press the trigger several times.

## 10. Warranty terms

The basis for all warranty claims is the complete pressure cup gun and the proof of purchase. Damage caused by improper handling of the pressure cup gun is not covered by the warranty.

If you have any questions, please indicate the type description or the article number of the pressure cup gun.

- In conformity with legal regulations, you receive a 24-month warranty on all products against material and manufacturing defects.

Excluded from the warranty:

- Wear parts.
- Damage caused by improper use.
- Damage caused by lack of maintenance.
- Damage caused by dirt.
- Damage caused by untreated compressed air.

If warranty claims are made, the pressure cup gun must be in its original condition.

## 11. Address

In case of service your sales representative is at your side or contact the following address:

Vaupel GmbH  
Gerätebau & Drucklufttechnik  
Am Forsthaus 6  
35713 Eschenburg-Simmersbach  
Germany  
Telephone: +49 (0) 2774 80069-0  
E-Mail: [info@vaupel-gmbh.de](mailto:info@vaupel-gmbh.de)  
Internet: [www.vaupel-gmbh.de](http://www.vaupel-gmbh.de)

**Notice:** We reserve the right to make technical changes. Illustrations may differ from the original. We assume no liability for printing errors.

## 12. EC-declaration of conformity

### EC-declaration of conformity

In accordance with the EC Machine Directive 2006/42/EC,

Type of gun: Pressure cup gun

Type designation: Type 3000 DV / DVR

Type description: Pressure cup spray gun

Article number Manufacturer: 30001, 30411, 30112, 30401

Is developed, designed and manufactured in accordance with the above EC Directives, under the general responsibility of

Company: Vaupel GmbH  
Gerätebau & Drucklufttechnik  
Am Forsthaus 6  
35713 Eschenburg-Simmersbach

The technical documentation is complete.

The following harmonised standard has been applied:

**DIN EN ISO 12100 - Sicherheit von Maschinen – Allgemeine Gestaltungsleit-  
sätze - Risikobeurteilung und Risikominderung**

The operating instructions belonging to the machine are available in the original version and in the respective national language.

Simmersbach, 01.04.2020

Place, Date



Signature, Managing director



**13. Spare parts list**

<b>Pos.</b>	<b>Article no.</b>	<b>Description</b>
1	---	Gun body
2	50 3909 005	Trigger
3	30 1102 006	Lever axis
4	60 3100 029	Lock washer
5	83002	Nozzle needle complete
6	60 3104 007	Spring for nozzle needle
7	30 1122 005	Stop screw
8	80158	Valve bolt
9		O-ring 1,5 x 0,75 mm
10		Valve seal
11	60 3103 003	Spring for valve
12	60 4100 362	O-ring 8 x 1 mm
13	30 1120 002	Locking screw
14	40 4100 003	Needle seal Teflon
15	60 4100 364	O-ring 5 x 1 mm
16	30 1421 012	Needle gland
17	60 4100 366	O-ring 8 x 2,5 mm
18	83003	Spray nozzle 3000
19	60 4100 314	O-ring 10 x 2 mm
20	30 1411 007	Air nozzle SW 17 mm
21	83313	O-ring 15 x 2 mm
22		Adapter 3000
23		O-Ring 33 x 2 mm
24	80502	Exhaust air valve (only with 3000 DVR)
25	10 2112 006	Container lid with ¼"
26	60 4100 060	O-ring 84 x 4 mm
27	83005	U-Cup 12 x 18 x 4.5 x 1.6 (only with 3000 DVR)
28		Fixing screw
29	60 3129 017	Riser pipe 250 mm long
30	60 3100 028	Serrated ring ZA 16
31	60 3106 002	Pressure spring for pressure cap
33	40 4101 032	Pressure cap
34	10 2109 004	Pressure container
35	83004	Air volume regulation device (optional)
36	30 1423 002	Compressed air connection D
37	30 1423 001	Compressed air connection F (optional)
38	30 1413 002	Compressed air connection CH (optional)
39	30 1422 001	Compressed air connection ¼" AG (optional)

## **14. Notices**