


Cavity sealing- Pressure cup gun 3200 DVR

Art. no.: 32001 / 32402



Thank you very much for the trust you have placed in us and our products.



Please read the operating manual first before using the spray gun.

This operating and maintenance manual contains important information required for the safe and trouble-free operation of your pressure cup gun. For this reason, always keep this operating manual with the pressure cup gun.

General notice:

This pressure cup gun was developed for certain applications. We explicitly point out that this pressure cup gun must not be modified and/or used in a way that does not correspond to its intended use.

Content:

| | |
|--|----|
| 1. Technical data | 3 |
| 2. Extent of delivery | 3 |
| 3. Intended use | 3 |
| 4. Features | 3 |
| 5. Safety instructions | 3 |
| 6. Installation / end of work | 5 |
| 7. Maintenance and care | 5 |
| 8. Storage | 6 |
| 9. Troubleshooting | 6 |
| 10. Warranty terms | 6 |
| 11. Address | 7 |
| 12. EC-declaration of conformity | 8 |
| 13. Spare parts list | 9 |
| 14. Notices | 10 |

1. Technical data

| Description | 3200 DVR |
|---------------------------|---------------------------|
| Operating pressure | 2-8 bar |
| Maximum pressure | 8 bar |
| Container volume | 1.400 ml |
| Connection thread Air | ¼" |
| Compressed air connection | via quick coupling |
| Adjustable spray pattern | Material flow adjustable |
| Measurement | 387 x 178 x 95 mm |
| Measurement cardboard | 415 x 247 x 110 mm |
| Net weight | approx. 1430 g |
| Gross weight | approx. 1.754 g |
| Weight 3900 WH 02/04 | 150 g * |
| Required air quality | filtered, condensate-free |

* included with 3200 DVR set

2. Extent of delivery

Pressure cup gun, compressed air connection, operating manual.

Additionally included with 3200 DVR set: Hose set 3900 WH 02 or 04..

3. Intended use

This pressure cup gun is a compressed air operated quality tool for professional use. It is suitable for processing liquid media in the form of commercially available 1 litre cans.

4. Features

The effectiveness of the 3200 DVR pressure cup gun is based on overpressure. For this purpose, pressure is built up in the pressure container by means of an air duct integrated in the gun body. This conveys the material present in the pressure container via a riser pipe to the material nozzle. When the lever is pressed, the material flows out of the material nozzle where it is mixed with the spray air.

5. Safety instructions



This pressure cup gun is not suitable for alkaline and acidic media.

Such media must not be processed with this pressure cup gun!!!

Protect yourself and the environment by taking appropriate precautions against the risk of accidents and observe the following instructions in your own interest:



- The operator must ensure proper operation.
- Do not bring compressed air and/or medium into contact with skin or eyes.
- Never direct the spray jet at animals, people or yourself.
- Keep children and pets away from the operating area.
- No manipulations, emergency repairs or misappropriations may be carried out on the pressure cup gun.
- Pressure cup guns may only be operated and maintained by instructed persons.
- Repairs must only be carried out by qualified persons.

The following applies to all maintenance and repair work:



- It is essential to disconnect the pressure cup gun from the compressed air connection before carrying out maintenance or repair work.
- Only use original spare parts.
- The maximum working pressure must not be exceeded (see point 1 "Technical data"). The working pressure must be adjusted via a (filter) pressure reducer.
- Only use compressed air as energy source.
- The compressed air connection may only be made via quick coupling.
- When working with the pressure cup gun, wear the necessary protective clothing, protective goggles, work gloves, ear protection if necessary and a respirator mask.
- If there are leaks in the device or other operating faults, the device must be disconnected from the compressed air supply immediately and the cause of the fault must be eliminated.
- Open fire, sparks or smoking is prohibited.
- Beware of flammable materials.
- Processed media and cleaning media must be disposed of in an environmentally friendly manner.
- The disposal of the compressed air device must be carried out according to the valid legal regulations.

6. Installation / end of work

Preparing the gun for the first start-up: Screw in the compressed air connection and tighten it firmly using a 13 mm open-end wrench or ring spanner, if necessary glue it in place.

Start-up: Unscrew the pressure container. Pierce the protective foil of the 1 litre can and place it in the pressure container. Then dip the riser pipe into the medium and screw the gun with the container lid onto the pressure container hand-tight. Do not use any tools for this! Plug the connection nipple of the hose (type 3900 or 3901) onto the quick coupling and let it engage. Connect the gun to the compressed air supply via the quick coupling of the air connection. By pressing the trigger you put the pressure cup gun into operation.



Attention:

Wear heat-resistant gloves when using heated medium. Danger of burns!

The spray pattern can be influenced by the following factors::

- Material quantity via stop screw/nozzle need
- Adjusting the intake pressure (optional)
- Distance between hand spray nozzle and object
- Angular position of the hand spray nozzle to the object

End of work: Vent the pressure container using the exhaust air valve (pos.24). Disconnect the device from the compressed air supply after each use. Clean the device according to the instructions given in point 7.



Attention:

Never operate the trigger while the container is under pressure but the pressure cup gun is not connected to the compressed air source. This can push the medium into the air ducts and render the pressure cup gun unusable!

7. Maintenance and care

Clean the compressed air device after each use. Fill the pressure container with cleaner and flush the pressure cup gun and the hoses by putting the device into operation. We recommend benzine or commercially available turpentine-based detergents. **Do not use aggressive cleaning agents!** Observance of the maintenance instructions will ensure a long service life and trouble-free operation for this quality product.



Attention:

Pay attention to a proper disposal of the residues, which arise during the maintenance and care.

8. Storage

The compressed air tool must be stored under the following conditions:

- If residual material is present, store only upright.
- Carefully clean the pressure cup gun after each use.
- Store in a dry and dust-free place.
- Do not expose to liquids and/or aggressive chemicals.
- Keep out of the reach of children.

9. Troubleshooting

In all cases of malfunction, please first check whether there is sufficient compressed air available, whether the spray material can still be processed, whether the expiry date has passed or whether the material has dried out.

- **Gun sprays messy**
Possible cause: Operating pressure too low, nozzles are dirty.
Solution: Increase operating pressure, clean nozzles.
- **Gun does not spray any material**
Possible cause: The riser pipe and/or the spray nozzle are clogged.
Solution: Clean clogged parts.
- **Air escapes from the spray nozzle even though the trigger is in its initial position.**
Possible cause: Valve bolt is jammed.
Solution: Pour oil onto the valve bolt and/or into the compressed air intake. Operate the trigger several times.
- **Material exits the spray nozzle even though the trigger is in its initial position.**
Possible cause: Nozzle needle is jammed / dirty.
Solution: Clean the nozzle needle, apply oil to the nozzle needle and/or slightly re-duce the pressure on the nozzle needle seal using a 9mm wrench. In order to ensure error-free use, a clamping effect on the nozzle needle seal must remain. Press the trigger several time.

10. Warranty terms

The basis for all warranty claims is the complete pressure cup gun and the proof of purchase. Damage caused by improper handling of the pressure cup gun is not covered by the warranty.

If you have any questions, please indicate the type description or the article number of the spray gun.

- In conformity with legal regulations, you receive a 24-month warranty on all products against material and manufacturing defects.

Excluded from the warranty:

- Wear parts.
- Damage caused by improper use.

- Damage caused by lack of maintenance.
- Damage caused by dirt.
- Damage caused by untreated compressed air.

If warranty claims are made, the pressure cup gun must be in its original condition.

11. Address

In case of service your sales representative is at your side or contact the following address:

Vaupel GmbH
Gerätebau & Drucklufttechnik
Am Forsthaus 6
35713 Eschenburg-Simmersbach
Germany
Telephone: +49 (0) 2774 80069-0
E-Mail: info@vaupel-gmbh.de
Internet: www.vaupel-gmbh.de

Notice: We reserve the right to make technical changes. Illustrations may differ from the original. We assume no liability for printing errors.

12. EC-declaration of conformity

EC-declaration of conformity

In accordance with the EC Machine Directive 2006/42/EC,

Type of gun: Pressure cup gun

Type designation: Type 3200 DVR

Type description: Cavity sealing pressure cup gun

Article number Manufacturer : 32001, 32402

Is developed, designed and manufactured in accordance with the above EC Directives, under the general responsibility of

Company: Vaupel GmbH

Gerätebau & Drucklufttechnik

Am Forsthaus 6

35713 Eschenburg-Simmersbach

The technical documentation is complete.

The following harmonised standard has been applied :

DIN EN ISO 12100 - Sicherheit von Maschinen – Allgemeine Gestaltungsleit-sätze - Risikobeurteilung und Risikominderung

The operating instructions belonging to the machine are available in the original version and in the respective national language.

Simmersbach, 01.04.2020

Place, Date



Signature, Managing director

13. Spare parts list

| Pos. | Article no. | Description |
|-------------|--------------------|--|
| 1 | --- | Gun body |
| 2 | 50 3909 005 | Trigger |
| 3 | 30 1102 006 | Lever axis |
| 4 | 60 3100 029 | Lock washer |
| 5 | 83010 | Nozzle needle complete |
| 6 | 60 3104 007 | Spring for nozzle needle |
| 7 | 30 1122 005 | Stop screw |
| 8 | 80158 | Valve bolt |
| 9 | | O-ring 1.5 x 0.75 mm |
| 10 | | Valve seal |
| 11 | 60 3103 003 | Spring for valve |
| 12 | 60 4100 362 | O-ring 8 x 1 mm |
| 13 | 30 1120 002 | Locking screw |
| 14 | 40 4100 003 | Needle seal Teflon |
| 15 | 60 4100 364 | O-ring 5 x 1 mm |
| 16 | 30 1421 012 | Needle gland |
| 17 | 60 4100 366 | O-ring 8 x 2.5 mm |
| 18 | 30 2122 005 | Nozzle head |
| 19 | 20 1413 001 | Quick coupling |
| 20 | See accessory list | Cavity spray hose (accessory) |
| 21 | 83313 | O-ring 15 x 2 mm |
| 22 | | Adapter 3000 |
| 23 | | O-ring 33 x 2 mm |
| 24 | 80502 | Exhaust air valve |
| 25 | 10 2112 006 | Container lid with ¼" |
| 26 | 60 4100 060 | O-ring 84 x 4 mm |
| 27 | 83005 | U-cup 12 x 18 x 4.5 x 1.6 |
| 28 | | Fixing screw |
| 29 | 60 3129 017 | Riser pipe 250 mm long |
| 30 | 60 3100 028 | Serrated ring ZA 16 |
| 31 | 60 3106 002 | Pressure spring for pressure cap |
| 32 | 40 4101 032 | Pressure cap |
| 33 | 10 2109 004 | Pressure container |
| 34 | 83004 | Air volume regulation device (optional) |
| 35 | 30 1423 002 | Compressed air connection D |
| 36 | 30 1423 001 | Compressed air connection F (optional) |
| 37 | 30 1413 002 | Compressed air connection CH (optional) |
| 38 | 30 1422 001 | Compressed air connection ¼" AG (optional) |

14. Notices